



PRODUCT NUMBER: 6246130

**BACOU PRO'CLEAN BLACK
S2 SRC**

Breathable water resistant microfibre upper. PU2D outsole injected. SRC certified. 200J Spacium toe cap in injected polymer. Complies with EN ISO 20345:2011 Standard.



Overview

Reference Number
6246130

Product Type
Footwear

Brand
Honeywell

Brand formerly known as
BACOU

Industry

- Catering
- Food Industries
- Industrial Cleaning
- Laboratory
- Medical and Pharmaceutical
- Services

Product Use

- Safety shoes for professional use. Bacou Pro'Clean Black S2 SRC model is comfortable and easy to put on.

Features & Benefits

Feature
EN ISO 20345:2011 certified. SRC certified

Benefit

Ensures better protection

Feature

Breathable water resistant microfibre upper

Benefit

Maximum comfort and lightness

Feature

No stitching on the upper

Benefit

Limits contamination; easy care

Feature

Dual density polyurethane outsole

Benefit

High-performance, light & flexible

Technical Description**Sizes**

EU : 35-48 / UK: 3 - 12

Upper

Breathable water resistant microfibre upper

Toe Cap

200J SPACIUM™ toe cap in injected polymer. Non-metallic: 50% lighter than steel. Extra-wide for greater comfort: suits all foot types. Non magnetic. Thermal insulator. Unalterable.

Insole

Dual density PU foam for intensive use. Removeable for easy care. Antibacterial for a longer life span and to prevent odour. Antistatic for optimal efficiency. Comfortable heel pads. Evacuation channels.


Outsole

Dual density polyurethane: PU 2D. Comfort layer of density: 0.5 (guarantees lightness and flexibility, ensures shock absorption and protects against changes in temperature). Outsole layer of density: 1 (resistance to abrasion, fuel oil and grease). High slip resistance due to well defined cleat design, wide, deep and self-cleaning. SRC certified: SRA: on ceramic plates: flat 0,45 (minimum standard: 0,32) heel 0,46 (minimum standard: 0,28) / SRB: on steel floor: flat 0,24 (minimum standard: 0,18) heel 0,24 (minimum standard: 0,13). Energy absorption capacity > 20 joules. Excellent resistance to abrasion: volume loss < 150 mm³ (with a load of 10 N = 1 kg). Extension before tearing: 650%. Optimised resistance to repeated flexing > 60,000 (standard >30,000). Resistant to acids and alkalis: limited to low concentrations.

Additional Features

- SRC

Certifications

 E.C. Declaration of Conformity

EC Category PPE

2

EC Certificate Number

0075/797/161/04/12/0262

EC Attestation

 6246130_BACOU PROCLEAN BLACK _S2 SRC

Certifications

- EN ISO 20345:2011


REACH

EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Literature & Documents

 E.C. Declaration of Conformity

 User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

[http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/footwear\(200j_toe_cap\)/4294967896/1033.aspx](http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/footwear(200j_toe_cap)/4294967896/1033.aspx)

Photos & Images

6246130_BACOU PROCLEAN BLACK S2 SRC_290

<http://www.honeywellsafety.com/assets/0/324/1042/1045/5b03c386-a91c-4f7d-80c3-fb890467a4d7.jpg?n=8681>

6246130_BACOU PROCLEAN BLACK _B_ S2 SRC

<http://www.honeywellsafety.com/assets/0/324/1042/1045/ce26a2c6-d41e-435a-82f7-59a15755f00e.jpg?n=1117>

6246130_BACOU PROCLEAN BLACK _C_ S2 SRC

<http://www.honeywellsafety.com/assets/0/324/1042/1045/bc3d4707-420e-4dd2-a37a-7da5000d7097.jpg?n=2893>

6246130_BACOU PROCLEAN BLACK _SEMELLE S2 SRC

<http://www.honeywellsafety.com/assets/0/324/1042/1045/1b675568-ba22-41f5-96f7-83c1fa9bbd3a.jpg?n=4214>

Maintenance**Life Cycle**

- We advise that the footwear should be used in the limit of 3 years following the manufacturing date, which figures on the footwear.
- After this time limit, certain factors such as: exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE.

Storage Information

- Footwear should be stored in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels.

Care Instructions

- After use leave your footwear to dry in an aired place away from heat. Remove any excess dust or dirt with a brush. Remove any marks using a damp cloth and soap if necessary.
- Finally polish any grain or pigmented leathers using a commercially available shoe care product.

Honeywell

[View other region sites](#)
© 2013 Honeywell International Inc.