



PRODUCT NUMBER: 6246127

BACOU PRO'CLEAN S2 SRC

Breathable water resistant microfibre upper. PU2D outsole injected. SRC certified. 200J Spacium toe cap in injected polymer. Complies with EN ISO 20345:2011 Standard.

Overview	<p>Reference Number</p> <p>6246127</p> <p>Product Type</p> <p>Footwear</p> <p>Brand</p> <p>Honeywell</p> <p>Brand formerly known as</p> <p>BACOU</p> <p>Industry</p> <p>Catering Food Industries Industrial Cleaning Laboratory Medical and Pharmaceutical Services</p> <p>Product Use</p> <ul style="list-style-type: none">Safety shoes for professional use. Bacou Pro'Clean S2 SRC model is comfortable and easy to put on.
----------	---

Features & Benefits	<p>Feature</p> <p>EN ISO 20345:2011 certified. SRC certified</p> <p>Benefit</p> <p>Ensures better protection</p>
---------------------	--

Feature

Breathable water resistant microfibre upper

Benefit

Maximum comfort and lightness

Feature

Upper in white

Benefit

Adapted to different environments/industries

Feature

No stitching on the upper

Benefit

Limits contamination; easy care

Feature

Dual density polyurethane outsole

Benefit

High-performance, light & flexible

Technical Description**Sizes**

EU: 35-49 / UK: 3-13,5

Table Size**Upper**

Breathable water resistant microfibre upper

Toe Cap

200J SPACIUM™ toe cap in injected polymer. Non-metallic: 50% lighter than steel. Extra-wide for greater comfort: suits all foot types. Non magnetic. Thermal insulator. Unalterable.

Insole

Dual density PU foam for intensive use. Removeable for easy care. Antibacterial for a longer life span and to prevent odour. Antistatic for optimal efficiency. Comfortable heel pads. Evacuation channels.


Outsole

Dual density polyurethane: PU 2D. Comfort layer of density: 0.5 (guarantees lightness and flexibility, ensures shock absorption and protects against changes in temperature). Outsole layer of density: 1 (resistance to abrasion, fuel oil and grease). High slip resistance due to well defined cleat design, wide, deep and self-cleaning. SRC certified: SRA: on ceramic plates: flat 0,45 (minimum standard: 0,32) heel 0,46 (minimum standard: 0,28) / SRB: on steel floor: flat 0,24 (minimum standard: 0,18) heel 0,24 (minimum standard: 0,13). Energy absorption capacity > 20 joules. Excellent resistance to abrasion: volume loss < 150 mm³ (with a load of 10 N = 1 kg). Extension before tearing: 650%. Optimised resistance to repeated flexing > 60,000 (standard >30,000). Resistant to acids and alkalis: limited to low concentrations.

Additional Features

- SRC

Certifications

 E.C. Declaration of Conformity


EC Category PPE

2

EC Certificate Number

0075/797/161/04/12/0262

EC Attestation

 6246127-Bacou Pro Clean S2 SRC

Certifications

- EN ISO 20345:2011

REACH


EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Literature & Documents

 E.C. Declaration of Conformity

 User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

[http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/footwear\(200j_toe_cap\)/4294967896/1033.aspx](http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/footwear(200j_toe_cap)/4294967896/1033.aspx)

Photos & Images


6246127_BACOU PROCLEAN S2 SRC_290

<http://www.honeywellsafety.com/assets/0/324/1042/1045/713d90c0-9065-4ae8-98c4-5a196cfc585e.jpg?n=4964#6246127>

6246127_BACOU PROCLEAN S2 SRC_SEMELLE

<http://www.honeywellsafety.com/assets/0/324/1042/1045/42e5c1d3-e133-4f76-adee-7d658e62a583.jpg?n=6213>

Additional Information**User Manual**

 User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

Maintenance**Life Cycle**

- We advise that the footwear should be used in the limit of 3 years following the manufacturing date, which figures on the footwear.
- After this time limit, certain factors such as: exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE.

Storage Information

- Footwear should be stored in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels.

Care Instructions

- After use leave your footwear to dry in an aired place away from heat.
- Remove any excess dust or dirt with a brush. Remove any marks using a damp cloth and soap if necessary.
- Finally polish any grain or pigmented leathers using a commercially available shoe care product



[View other region sites](#)
© 2013 Honeywell International Inc.