Honeywell



PRODUCT NUMBER: 6246129 BACOU SUPER PRO'CLEAN S2 SRC

Breathable water resistant microfibre upper. PU2D outsole injected. SRC certified. 200J Spacium toe cap in injected polymer. Complies with EN ISO 20345:2011 Standard.

Honeywell

Overview

Reference Number 6246129

Product Type Footwear

Brand Honeywell

Brand formerly known as BACOU

Industry

Catering
Food Industries
Industrial Cleaning
Laboratory
Medical and

 Medical and Pharmaceutical

Services

Product Use

 Safety shoes for professional use. Bacou Super Pro'Clean S2 SRC model is comfortable and easy to put on.

Features & Benefits

Feature High upper

6246129_ Bacou Super Pro'Clean S2 SRC

Benefit

Prevents liquid and dust from entering the shoe

Feature EN ISO 20345:2011 certified. SRC certified

Benefit Ensures better protection

Feature Breathable water resistant microfibre upper

Benefit Maximum comfort and lightness

Feature No stitching on the upper

Benefit Limits contamination; easy care

Feature Dual density polyurethane outsole

Benefit High-performance, light & flexible

Technical Description

EU: 35-48 / UK: 3-12

Table Size

Upper

Sizes

Breathable water resistant microfibre upper

Toe Cap

200J SPACIUM[™] toe cap in injected polymer. Non-metallic: 50% lighter than steel. Extra-wide for greater comfort: suits all foot types. Non magnetic. Thermal insulator. Unalterable.

Insole

Dual density PU foam for intensive use. Removeable for easy care. Antibacterial for a longer life span and to prevent odour. Antistatic for optimal efficiency. Comfortable heel pads. Evacuation channels

Outsole

Dual density polyurethane: PU 2D. Comfort layer of density: 0.5 (guarantees lightness and flexibility, ensures shock absorption and protects against changes in temperature). Outsole layer of density: 1 (resistance to abrasion, fuel oil and grease). High slip resistance due to well defined cleat design, wide, deep and self-cleaning. SRC certified: SRA: on ceramic plates: flat 0,45 (minimum standard: 0,32) heel 0,46 (minimum standard: 0,28) / SRB: on steel floor: flat 0,24 (minimum standard: 0,18) heel 0.24 (minimum standard: 0.13). Energy absorption capacity > 20 joules. Excellent resistance to abrasion: volume loss < 150 mm3 (with a load of 10 N = 1 kg). Extension before tearing: 650%. Optimised resistance to repeated flexing > 60,000 (standard >30,000). Resistant to acids and alkalis: limited to low concentrations.

Additional Features

SRC

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

EC Certificate Number

0075/797/161/04/12/0262

EC Attestation

6246129_ Bacou Super Pro Clean S2 SRC

Certifications

• EN ISO 20345:2011

REACH

EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012 http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/footwear (200j_toe_cap)/4294967896/1033.aspx

Photos & Images

6246129_BACOU SUPER PROCLEAN S2 SRC _290 http://www.honeywellsafety.com/assets/0/324/1042/1045/f717286a-b74a-4a7b-a525a403955a1f80.jpg?n=8638

6246129_BACOU SUPER PROCLEAN S2 SRC _600 http://www.honeywellsafety.com/assets/0/324/1042/1045/1153ac87-4b48-4d87-9943e3eada0957b9.jpg?n=8065

6246129_BACOU SUPER PROCLEAN S2 SRC b http://www.honeywellsafety.com/assets/0/324/1042/1045/47613c6e-32c2-4ad0-848cb5a797adbb1d.jpg?n=3099

6246129_BACOU SUPER PROCLEAN S2 SRC c

6246129_ Bacou Super Pro'Clean S2 SRC

http://www.honeywellsafety.com/assets/0/324/1042/1045/e58eff99-be81-4666-afc6-49c318ff5f44.jpg?n=8177

6246129_BACOU SUPER PROCLEAN S2 SRC_SEMELLE http://www.honeywellsafety.com/assets/0/324/1042/1045/42e5c1d3-e133-4f76-adee-7d658e62a583.jpg?n=1894

Life Cycle

Maintenance

• We advise that the footwear should be used in the limit of 3 years following the manufacturing date, which figures on the footwear.

 After this time limit, certain factors such as: exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE.

Storage Information

• Footwear should be stored in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels.

Care Instructions

- After use leave your footwear to dry in an aired place away from heat.
- Remove any excess dust or dirt with a brush. Remove any marks using a damp cloth and soap if necessary.
- Finally polish any grain or pigmented leathers using a commercially available shoe care product.

Honeywell

View other region sites © 2013 Honeywell International Inc.