

# ECONOMYARM®

The affordable choice



Wall bracket  
is included  
(EA-2,-3 and -4)

Ball bearing  
suspension

Ratchet damper  
standard

2, 3 or 4 meter  
working radius

Detachable  
steel hood



© Copyright. All rights reserved.

## PLYMOVENT AB

Industrigatan 26, 212 14 Malmö, Sweden  
Tel: +46 40 30 31 30, Fax: +46 40 30 31 40  
www.plymovent.com, info@plymovent.com

## PLYMOVENT LTD

Marley Way, Southam Rd,  
Banbury OX16 2RA, England  
Tel. (01295) 25 93 11, Fax (01295) 27 17 50  
www.plymovent.com, info@plymovent.co.uk

**PLYMOVENT®**

## A quality choice at a price anyone can afford

Our new value for money, extraction arm. The EconomyArm is in the low price range but gives performance and features that previously only more expensive arms could offer. A free wall bracket, ball bearing suspension, hood collar and hood are from the well known KUA arm.

## FEATURES AND BENEFITS

The EconomyArm is a ball-bearing suspended extraction arm that comes in 2, 3 or 4m length, Ø 160 mm. The spring balanced support mechanism and the friction brakes provide an extraction arm with smooth operation within the whole working radius. The standard complementary wall bracket (EA-2,-3 and -4) has a Ø 160 mm

duct connection included but can also hold a PlymoVent FUA fan directly without any special brackets. Ball bearing suspension is standard.

The support mechanism is surrounded by a high quality extraction hose. Safety mesh and ratchet air control damper in the removable hood. The hood can also be fitted with a 20 watt.



### TECHNICAL DATA

Product no.:	EA-2	EA-3	EA-3-S	EA-4	EA-4-S
Working radius:	2 m	3 m	3 m	4 m	4 m
Weight (kg):	17 kg	18.5 kg	15 kg	20.5 kg	17 kg

Tube/hose diam: Ø160 mm

Rec. airvolume: 800 - 1200 m<sup>3</sup>/h

#### Accessories

Halogen light kit: HL-20/24-160

Transformer

115/24 V: TR-24/75

Extension columns: PA-110 (1,1m) PA-220 (2,2m)

Wall bracket: 500538 Note! Standard on EA-2, EA-3 and EA-4.

## Quality from top to bottom!



The standard supplied wall bracket (EA-2,-3 and-4) has ball bearings and friction brake for long lasting and smooth operation..



Strong, slim designed support mechanism ensures stability and a minimum of restrictions.



High quality extraction hose is used for extended lifetime (wear & tear).



Hood collar with 360° ring handle and ratchet damper. Detachable spun steel hood.

[www.plymovent.com](http://www.plymovent.com)