455 Skystep™



- Ergonomically engineered, the SkyStep™ utilizes
 the power of air. The mat is designed to suction to
 the ground to prevent the mat from shifting while
 trapping air in its chambers. These air pockets
 combined with the resiliency of the rubber create
 an ultimate cushioning effect while keeping the
 mat lightweight.
- The bubble surface provides a sure footing and optimal ergonomic effects in stationary standing positions.
- Made of high quality natural rubber for maximum durability and excellent standing comfort.
- Moulded bevelled edges on all four sides to prevent tripping on the mat.
- Clean by sweeping or vacuuming.
- Designed to yield a long service life.
- Resistant to most chemicals and extreme temperatures.
- Free of silicone therefore safe for vehicle painting facilities.



455 Skystep™

	PR	RODUCT SPECIFICATIONS	
Designation	Industrial matting		
Туре	Anti-fatigue		
Description	Standalone Rubber Mats		
Material	100% natural rubber compound - Not for use in contact with oils and animal fats.		
Process	Compression moulding		
Category	Better		
Recommended use	Medium duty – dry industrial environments		
Colours	Black		
Weight	10 kg/m²		
Thickness	13 mm		
Standard sizes	60 cm x 90 cm 90 cm x 120 cm 90 cm x 150 cm		
Custom sizes	N/A		
Special remarks			
		PRODUCT TESTING	
Tests		Norms	Results
Compression deflection		U.S.	
		ASTM D575	
		ASTM D575	
Foam battery		ASTM D3574	
Abrasion resistance		ASTM D3884-01	
	1000 Cycles		0.824
	5000 Cycles		
Static coefficient of friction		ASTM C1028-96	
Elongation		DIN 53455-6-4	210%
Breaking load		ASTM D412	4.80 Mpa
Graves tear strength		ASTM D 1004	10.5 N/mm
Hardness		ASTM D2240-02	67 Shore A
Anti-slip		DIN 51130 and BG-RULE BGR181	R9
		FIRE TESTING	
	Critical radiant flux	ASTM E-648	
	Fire veterder or	DIN4102	
	Fire retardancy	EN 13501-1	
	Flammability test	ASTM D2859	5 min.
ESD		ANSI ESD S7.1 50% Humidity	
Sustainability		 Recyclable material Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 	

