

# 563RD Sanitop Deluxe™ Red



- Designed to withstand harsh chemicals, this anti-fatigue mat offers simple solution to almost any industrial or foodservice application.
- Ergonomic benefit of 20 mm thickness worker rubber platform -more comfort - more durability.
- Straight edges allow coverage of any area through linking the mats lengthwise or side-by-side, held together by connectors.
- Optional attachable vinyl bevels for easy side or front access.
- Red or blue is suitable for grease resistance.
- Cleaning with detergent and water jet is recommended for extended service life.
- Drainage holes and raised studs provide aeration and allow fluids and debris to fall through, keeping the surface clear.
- Aggressive slip resistant surface.
- Made of tough compound, designed to yield a long service life.

# 563RD Sanitop Deluxe™ Red

PRODUCT SPECIFICATIONS			
Designation		Industrial Matting	
Type		Anti-fatigue / anti-slip	
Description		Duckboard, open ring mat, drainage holes, aggressive slip-resistance surface.	
Material		Red: 75% nitrile rubber compound	
Process		Compression moulding	
Category		Best	
Recommended use		Heavy duty – wet / dry industrial environments. Food service, diary and fish industry, abattoirs	
Colours		Red	
Weight		12.3 kg/m²	
Thickness		20 mm	
Standard sizes		91 cm x 152 cm	
Custom sizes		Connectors, attachable yellow ramps 91 cm piece, 152 cm piece, per linear meter	
Special remarks		Optional attachable vinyl bevels for easy side or front access	
PRODUCT TESTING			
Tests		Norms	Results
Compression deflection		U.S.	
	1.4 kg/cm²		
	2.8 kg/cm²		
Foam battery		ASTM D3574	
Abrasion resistance		ASTM D3884-01	
	500 Cycles		
	1000 Cycles		
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.251.P.044985.07.09
Static coefficient of friction		ASTM C1028-96	
Elongation		ASTM D412	
Breaking load		ASTM D412	
Graves tear strength		ASTM D 1004	
Hardness		ASTM D2240-02	
Anti-slip		DIN 51130 and BG-RULE BGR181	
FIRE TESTING			
	Critical radiant flux	ASTM E-648	
	Fire retardancy	DIN EN 9239	
	Flammability test	ASTM D2859	
ESD		ANSI ESD S7.1 50% Humidity	
Sustainability		<ul style="list-style-type: none"><li>• Recyclable material</li><li>• Reach Compliant (Registration, Evaluation, Authorization and Re- striction of Chemicals)</li></ul>	