



**Honeywell Miller new Durahoist 3Pod
for confined spaces**

DuraHoist 3Pod: A single tripod adjustable to various confined space work situations. It is easy to transport and rapid to install.

- Easy to carry & move (leg profile ergonomic for hand grip)
- Easy & safe to install in less than 2 minutes (all legs open simultaneously, 1 knob fixing all legs together)
- Adaptable to different manhole sizes (1m – 1.50m – 2.50m)
- Certified to the last requirements of the EN 795:2012 class B (CN/TS 16415)
- Tested for 2 persons (up to 140kg each)



1m



1.50m



2.50m with webbing strap

What's a fall arrest system for confined spaces?


- 1 ANCHORAGE STRUCTURE**
Fall arrest system compliant to EN795:2012 B
- 2 WINCH**
Lifting load disposal. Machine Directive 2006/42/CEE
- 3 SELF RETRACTING LIFELINE WITH RETRIEVAL WINCH**
Compliant to EN 360:2002 and EN 1496:2006
- 4 SAFETY HARNESS**
Compliant to EN 361:2002



FEATURES AND BENEFITS

UNIQUE OPENING/FIXATION MECHANISM PLACED IN THE HEAD OF THE TRIPOD


- + Improved productivity
- + Fast adjusting and locking system for different leg opening angles (at 1m - 1.50m - 2.50m adapted to any manhole)
- + Number of attachment point on the head (3 holes + 1 eye-swivel)



PATENT PENDING

AVAILABLE TO ATTACH UP TO 2 PERSONS

and each weighing up to 140kg



ADJUSTABLE LEGS

- + End-stop leg at maximum length
- + Engraved marking for easy leg height adjustment (visual marking to position pin in hole)
- + Safe locking pin

ROBUST LEG DESIGN

- + Ergonomic leg's profile for hand grip
- + Resistant legs
- + Improved rescue when victim is pulled over to the side

EASY & QUICK CONNECTION BRACKETS FOR RAPID INSTALLATION OF ACCESSORIES ON OUTSIDE TRIPOD LEG:

- + Rescuing device to stop the fall and rescue the person
- + Winch for lifting loads (Maximal weight load limit 300kg)

LIGHTWEIGHT MATERIAL

- + Aluminium lightweight (16kg) and durable

STABILITY

- + Durable foot sole
- + Good stability and maximum slip resistance to all ground surfaces

PATENT PENDING



When closed, the legs are fixed and the tripod can be easily transported by gripping just one leg.



1.45m when closed for easy transport in small vehicles.

Specially designed for:

- Water Utilities (sewer lines, pumping & treatment station)
- Oil & Gas
- Electrical & Telecom companies
- Food and Chemical industries

DuraHoist 3Pod range

KITS		DuraHoist 3pod 1034430	MIGHTYLITE EVAC 15m Galvanized Wire Rope 1005149-A	MIGHTYLITE EVAC 15m Stainless Steel 1014390-A	MIGHTYLITE EVAC bracket for 15m Dura-Hoist 3pod 1034431	MIGHTYLITE EVAC 30m Galvanized Wire Rope 1005160-A*	MIGHTYLITE EVAC bracket for 30m Dura-Hoist 3pod 1034750*	DuraHoist Winch 15m Stainless Steel 1034611	DuraHoist Winch 30m Stainless Steel 1034612	Winch Bracket for 15m & 30m 1034613
										
1034910	3pod + MightEvac 15m G + Bracket	✓	✓		✓					
1034911	3pod + MightEvac 15m G + Winch 15m + 2 brackets	✓	✓		✓			✓		✓
1034912	3pod + MightEvac 15m SS + Bracket	✓		✓	✓					
1034913	3pod + MightEvac 15m SS + Winch 15m + 2 brackets	✓		✓	✓			✓		✓
1034914*	3pod + MightEvac 30m G + Bracket	✓				✓	✓			
1034915*	3pod + MightEvac 30m G + Winch 30m + 2 brackets	✓				✓	✓		✓	✓

*to come soon

Accessories	
1034511*	Bag for DuraHoist 3pod
1034432	Leg Plug set (3x Leg plug)
1034433	Leg Push pin set (3x Detent pin 70mm incl. lanyard and fixtures)
1034434	Foot Webbing (1x Complete feet webbing)
1034435	Foot Sole set (3x Rubber soles)



MAINTENANCE & REPAIR

- **Honeywell Fall protection's Miller Mechanical Service and repair program:**
as required by the European legislation for the class 3 PPE and reminded in the user guide, the full equipment must be yearly inspected according the procedure described in the checklist delivered with the device.
- **A repair guide** including list of tools, inspection sheet, photos. We remind you that this repair guide is only dedicated to the technicians trained by Honeywell (Miller Service Point).
- List of Spare parts & prices available on demand.

TRAINING

The use of our products is restricted to competent persons having undergone appropriate training (provided by an authorized person or organization) or under the supervision of a competent supervisor. The completion of this training must be recorded by the issue of a course certificate showing the date, location, name and company of the training organization, the full name of the user, etc.

Please contact our Honeywell Training department for more information.

HONEYWELL SAFETY PRODUCTS

United Kingdom

Phone: +44 (0) 1256 693 200
Fax: +44 (0) 1256 693 300
Email: info-uk.hsp@honeywell.com

International

Phone: +33 (0)1 49 90 79 79
Fax: +33 (0)1 49 90 71 04
Email: info-export.hsp@honeywell.com

FOR TECHNICAL QUESTIONS TECHNISERV

Northern and Central Europe
Phone: +49 (0) 9281/8302-205
Email: techniservnorth.hsp@honeywell.com

Southern Europe, UK, Ireland
Phone: +33 (0)2 48 52 40 42
Fax: +33 (0)2 48 52 40 76
Email: techniserv.hsp@honeywell.com



WATCH THE
PRODUCT VIDEO