

STEEL.



BOP 74 R

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> Temperatures up to +150 °C (only when used in conjunction with special internal fittings I/79 GW-R) metal spatter (MM) lateral deformation (LD) 		
	internal equipment		
Type	I/79 GD-R	I/79 GW-R	
Special feature	–	Testato a +150°C secondo i requisiti complementari	
Webbing	6 point	6 point	
Version	with screw cap	with screw cap (flame retardant)	
Eye protection	–	–	
Sweat band	real leather	real leather	
Cushion strip	standard	standard	
Chin strap suspension	4 point	4 point	
	helmet features		
Series	<ul style="list-style-type: none"> rain gutter 		
Factory fitted option	<ul style="list-style-type: none"> 16 mm double slots side ventilation (adjustable) hole in visor headtorch bracket cable loop all-round reflective film 		
Accessories	<ul style="list-style-type: none"> face protection neck protection hearing protection chin strap sweat bands reflective film 		
	version		
Size	1	2	3
Head circumference	52–56 cm	53–61 cm	59–63 cm
Colours	–	<ul style="list-style-type: none"> RAL 9016 RAL 1023 RAL 5017 RAL 3020 RAL 6024 RAL 2009 special metallic colours	<ul style="list-style-type: none"> RAL 9016 special metallic colours
Branding	printed		
Item, Size	Front, 4,5 × 4,5 cm	Side, 9 × 3 cm	
	parameter		
Shape	with extended neck section		
Material	UP-GF (Polyester fibreglass)		
Weight	approx. 460 g (size 2)		

APPLICATIONS

- hot environments
- chemical industry
- workplaces with high UV exposure
- workplaces with demanding and varied protection requirements
- high performance all-round helmets



Benefits

- +150°C**
I/79 GW-R
- Suited for tasks carried out in high ambient temperatures** (e.g. furnaces)
- available in 2 helmet shell sizes**
- Large protective surface** due to helmet with extended neck section
- rain gutter**
- suited to tasks with exposure to molten metal, for example**
- high lateral stiffness**
- retains shape at elevated temperatures
- high penetration resistance and impact toughness
- chemical resistant
- highly resistant to aging (long service life)
- very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings



SCHUBERTH