

# AlphaTec®

## VPS TYPE T

Formerly known as TRELLECHEM® VPS

## All-round and durable suit with excellent permeation times

- Non-encapsulating design, suitable for work in confined spaces
- Versatile suit with excellent chemical resistance and durability, both for the hazmat team and for the industrial user
- Offers very good abrasion and flame resistance
- One of the most popular suits in the AlphaTec® gas-tight suit range, with an extensive reference list
- Certified to the toughest standard in Europe - EN 943-2
- SOLAS approved



Anatomically designed face seal for optimum safety and comfort



Bayonet glove ring system for quick and simple glove exchange



The suit material is a combination of chloroprene rubber and a multilayer barrier, providing excellent chemical resistance as well as abrasion and flame resistance



Attached boots or sewn-in socks in the suit material



Gas-tight Protection




Re-usable



### Applications

- Chemical Handling
- Emergency Teams
- Fire & Rescue Service
- First Response
- Hazmat Teams
- Industrial and Tank Cleaning
- Law Enforcement
- Petrochemicals
- Shipping

### Material Construction



## PRODUCT INFORMATION

	AlphaTec® VPS TYPE T
<b>Design</b>	Non-encapsulating design type T (with face seal and without hump, BA worn outside the suit).
<b>Garment material</b>	Outer: Strong and flexible polyamide fabric coated with chloroprene rubber. Inner: Chloroprene rubber and a multilayer barrier laminate.
<b>Seams</b>	Stitched with aramid thread for superior strength and durability. Covered on the outside with a chloroprene rubber tape and on the inside with a welded-on barrier laminate tape.
<b>Face Seal</b>	Anatomically designed rubber face seal.
<b>Gloves &amp; Attachments</b>	2-part system with AlphaTec® #02-100 inner glove and AlphaTec® #38-628 Viton®/Butyl rubber glove. The gloves are attached with a Bayonet glove ring system, which offers quick and simple glove exchange.
<b>Footwear &amp; Attachments</b>	Sewn-in socks/booties made of the suit material. Alternatively attached black nitrile rubber safety boots with European approval as Firemen's boots. The boots are fixed with an ergonomically designed ring attachment, for simplified boot exchange.
<b>Zipper</b>	AlphaTec® HCR zipper, which includes a barrier film for increased chemical resistance. The zipper is closing downwards, for added safety, and is protected by a flap/splash guard.
<b>Ventilation</b>	A ventilation system is included as standard. For the safety of the wearer, it provides a constant level of overpressure inside the suit. The AlphaTec® Regulating valve MkII has 3 ventilation rates (2, 30 and 100 l/min) plus zero/off position. CEJN 221 male coupling for connection to the SCBA (requires separate connection hose). One overpressure valve on the chest.
<b>Colour</b>	Yellow or black/graphite.
<b>Sizes</b>	XXS - XXXL
<b>Included with each delivery</b>	<ul style="list-style-type: none"> <li>• 1 pce AlphaTec® Mini Hood for protection against inward leakage between mask and face seal, in case of jet spray from behind</li> <li>• 1 pair of cotton comfort inner gloves</li> <li>• 2 pcs extra locking pins for the Bayonet glove ring system</li> <li>• 1 pce Molycote lubrication for the O-rings in the Bayonet glove ring system</li> <li>• 1 pce grease stick for lubrication of the zipper</li> <li>• 1 pair of comfort silicone oversocks (only for suits with sewn-in socks)</li> <li>• 1 pce coat hanger</li> <li>• 1 pce AlphaTec® storage bag</li> </ul>
<b>Optional accessories</b>	<ul style="list-style-type: none"> <li>• Waist belt, internal</li> <li>• D-ring for holding small measuring instruments &amp; tools</li> <li>• Customised marking, e.g. digits, letters, logos</li> <li>• AlphaTec® #58-800 Overglove for improved cut &amp; puncture resistance</li> <li>• AlphaTec® SCBA Cover</li> <li>• Other accessories are available upon request</li> </ul>
<b>Standards &amp; Approvals</b>	<ul style="list-style-type: none"> <li>• EN 943-1:2015 + A1:2019</li> <li>• EN 943-2:2019</li> <li>• EN 1073-2:2002 (radioactive particle protection)</li> <li>• EN 14126:2003 (infective agent protection)</li> <li>• SOLAS</li> </ul>

For additional information, visit us at [protective.ansell.com](https://protective.ansell.com) or contact us at:

**Ansell Protective Solutions AB**  
Arenagatan 8B  
215 33 Malmö  
Sweden  
Tel. + 46 10 205 1800  
[order.protective@ansell.com](mailto:order.protective@ansell.com)

**North America**  
Ansell Healthcare LLC  
111 Wood Avenue South, Suite 210  
Iselin, NJ 08830, USA  
Tel. + 1 800 800 0444  
Fax. + 1 800 800 0445  
[info@ansell.com](mailto:info@ansell.com)

**Europe, Middle East and Africa**  
Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
Tel. + 32 2 528 74 00  
Fax + 32 2 528 74 01  
[info.europe@ansell.com](mailto:info.europe@ansell.com)

**Asia Pacific**  
Ansell Protective Solutions Singapore Pte. Ltd.  
237, Pandan Loop,  
#05-05 Westech Building  
128424 Singapore  
Tel. + 65 6908 4115  
[order.protective@ansell.com](mailto:order.protective@ansell.com)

**Latin America & Caribbean**  
Ansell Brazil Ltda.  
Rua das Figueiras 474 – 4º Andar  
Bairro Jardim  
SP 09080-300 Santo André, Brazil  
CNPJ: 03.496.778/0001-21  
+55 11 3356 3100  
[sac@ansell.com](mailto:sac@ansell.com)

## Performance Standards

