



## Filter A2, thread RD40x1/7"

Gas filter with RD40x1/7" thread





#### MALINA - Safety s.r.o.

Luční 11, 466 01 Jablonec n. Nisou, Czech Republic Tel.: +420 483 356 600, Email.: export@malina-safety.cz Web.: www.malina-safety.cz / www.clean-air.cz DA-098\_-\_500156\_-\_A2\_-\_EN

### © CleanAIR® All rights reserved

Revision.: 2021\_04\_15 Output.: 2021\_04\_15

## **TECHNICAL DATASHEET**

# *Filter A2, thread RD40x1/7*" Gas filter with RD40x1/7" thread



Technical specification	
Product code	50 01 56
Standards	A2 according to EN 14387 TH3 A2 according to EN 12941 TM3 A2 according to EN 12942
Weight	325 g
Dimensions	diameter 110 mm height 78 mm
Materials	filter housing: ABS filtration medium: activated charcoal
Thread	RD40x1/7" in accordance with EN 148-1
Storage conditions Operating conditions	– 10°C to + 55°C, humidity 20 - 95 % Rh + 0°C to + 60°C, humidity 20 - 95 % Rh

Group of contaminants	Protect against
А	Organic gases and vapours with a boiling point above 65 °C (e.g. toluene, benzene, styrene, kerosene, petrol, isobuthanol,)

Main requirements of EN 14387, EN 12941 and EN 12942			
Breathing resistance with clean filters	Required		
30 l/min	max. 260 Pa		
95 l/min	max. 980 Pa		
Gas filter capacity with test gas (30 l/min)	Required		
Cyclohexane C <sub>6</sub> H <sub>12</sub>	min. 35 min		
Gas filter capacity with test gas (80 l/min)	Required		
Cyclohexane C <sub>6</sub> H <sub>12</sub>	min. 70 min		

Filter A2, thread RD40x1/7" meets all requiremets and comply with stated norms. In addition, in most aspects the filter extensively surpasses the requirements of the standard. For more information please contact our sales department at export@malina-safety.cz.



## Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.