BLS SRL

via dei Giovi, 41 20032 Cormano (MI) - Italy t/f +39 0239310212 / 0266200473 info@blsgroup.it - www.blsgroup.com

BLS 3000 SERIES



REUSABLE FULL FACE MASKS WITH UNIVERSAL CONNECTION RD40

BLS 3000 series reusable full face masks are available with EPDM face seal. They are characterized by the high protection factor provided when used in combination with standard threaded filters EN148-1 (BLS 400 series) which protect against gas/vapors and toxic particulates.



UNIVERSAL CONNECTION

Standard thread connection according to EN 148-1, universal among all respiratory protection devices.

GLASS VISOR

It is a safety glass laminated with an EVA anti-fragmentation film which holds the pieces together if shattered. It gives a strong resistance against chemicals.



ANTI-FOG SYSTEM

Designed to avoid fogging on the visor through the control of the cold and hot air flows inside the mask instead of using surface treatments that can be easily spoiled.

FACE SEAL

Available in EPDM with FDA certification for a higher safety.

BLS SRL

via dei Giovi, 41 20032 Cormano (MI) - Italy t/f +39 0239310212 / 0266200473 info@blsgroup.it - www.blsgroup.com

BLS 3000 SERIES



REUSABLE FULL FACE MASKS WITH UNIVERSAL CONNECTION RD40

MATERIALS

FACE SEAL EPDM

VISOR BLS 3150 Polycarbonate (PC) VISOR BLS 3150V Multilayer glass

FILTER HOLDER Acrylonitrile Butadiene Styrene (ABS)

HARNESS Rubber HEAD PIECE EPDM

All components in direct contact with user's face are LATEX FREE

TECHNICAL DATA

MODEL	FACE SEAL	VISOR	DEVICE CLASS	CONNECTION	NPF (particle and combined filter)	NPF (gas filter)
BLS 3150	EPDM	Polycarbonate	2	EN148-1 (Universal)	1000*TLV (P3)	2000*TLV
BLS 3150V	EPDM	Glass	2	EN148-1 (Universal)	1000*TLV (P3)	2000*TLV

(TLV) Threshold Limit Value (NPF) Nominal Protection Factor

TRANSPORT

MODEL	CODE	WEIGHT (g)	Q.TY/BOX	Q.TY/CARTON	WEIGHT CARTON (Kg)
BLS 3150	8001064	510	1	4	2,40
BLS 3150V	8001066	712	1	4	3,05

STORAGE

SHELF-LIFE 10 years
TEMPERATURE -10°C/+50°C
RELATIVE HUMIDITY 80% max

CERTIFICATION

BLS full face masks are:

- Certified according to European Regulation 2016/425 (Personal Protective Equipments)
- Certified as PPE of III category, in presumption of conformity to harmonized standard EN 136:1998
- Certified and controlled according to Annex D by Italcert S.r.l. (Notified Body n°0426)
- CE marked

BLS management system is ISO 9001 certified.

BLS SRL

via dei Giovi, 41 20032 Cormano (MI) - Ítaly t/f +39 0239310212 / 0266200473 info@blsgroup.it - www.blsgroup.com

BLS 3000 SERIES



REUSABLE FULL FACE MASKS WITH UNIVERSAL CONNECTION RD40

AVAILABLE MODELS



Full face masks BLS 3150 - BLS 3150V

COMPATIBLE DEVICES



Filters BLS 400 series

DEVICES WITH THE SAME CONNECTION



Half mask BLS SGE46



Full face masks



BLS 5400 - BLS 5150

SELECTION GUIDE

GLASS VISOR_BLS 3150V

- It allows to have a high chemical resistance
- FULL FACE MASK VS HALF MASK
- Provides a much higher Nominal Protection Factor
- Protects face and eyes from dust, splinters and chemicals
- Supports filters with a total weight greater than 300 g

IMPORTANT

BLS declines any responsibility, direct or indirect, from any misuse of both devices and instructions. User is responsible for the determination of product compliance with the intended use.

