WHE00007











WHE00007-204 RED

TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL: ABS

INTERNAL SHELL: HD Polystyrene

HEADBAND: Soft PA Nylon



SIZE

Universal-adjustable from 51 to 63 cm



WEIGHT

480 g



STANDARD

EN 14052

Protection against front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1.2, 4.2.1.3, 4.2.1.4 shock energy absorption capacity Protection from impacts and penetration in conformitity with EN 397 Clause 5.1.1 Shock Absorption Clause 5.1.2 Penetration Resistance

EN 397 ADDITIONAL TESTS: LD

TEMPERATURE OF USE

WHE00007-202 YELLOW

-10°C/+50°C



CATEGORY

WHE00007-201

TECHNOLOGIES



2DRY

A quick-drying technical fabric that accelerates the dispersion of sweat and moisture to the surface of the helmet padding for a drier, more comfortable wear.



INTEGRATED LAMP CLIPS

Designed with four built-in, nylon lamp attachment points. treatment.



MICROMETRICAL ADJUSTMENT

The micrometrical size regulation system positioned at the rear of the helmet provides quick and precise adjustment, even when wearing gloves.



VENTILATION CHANNELS

Ten air intakes that enhance breathability and comfort.



EARMUFF ATTACHMENT SLOTS

Attachment points enable mounting earmuffs to helmet through bayonet adaptors.







Attachment points enable screw fastening of visor to helmet.







© 2022 KASK SPA. All rights reserved





PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J
Protection against side, front and rear impacts	K	5 kg from 1 m 50 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J

Required performance tests	K	Required	performance tests	S
----------------------------	---	----------	-------------------	---

Chinstrap release	K	>15 kg <25 kg
Retention system effectiveness	K	
Protection against side deformation	K**	

K** Additional tests performed to meet optional requirements

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.



SAFETY ACCESSORIES



WVI00018 VISOR V2 PLUS



WVI00024



WVI00003 VISOR FULL FACE



WVI00006



WHP00004/5/6 EARMUFFS



WAC00036/37 SUN SHIELD

DISCOVER MORE





SCAN FOR COMPLETE COLLECTION

© 2022 KASK SPA. All rights reserved



WLA00001/2/3 HEADLAMPS



WPA00007 WINTER CAP



WAC00020/24 NECK SHADE



WAC00032/33 NECK SHIELD RW







