

HONEYWELL OTTER PREMIUM PROTECT AIR

I Take a Step Ahead in Quality.

When it comes to safety, always settle for more. A world-renowned leader in safety innovation, Honeywell has joined hands with Otter, respecting its German quality values and committing to taking them further. Honeywell Otter Premium combines the heritages of the two brands, addressing workers in construction, chemical, or industrial maintenance and many other industries who need premium-quality protective work shoes with effective performances. With an iconic, traditional design, Honeywell Otter Premium footwear provides increased protection, enhanced stability and improved comfort. Benefit from great slip and anti-puncture protection, high shock absorption, antistatic properties plus high- and low-temperature resistance, being fully aware when your shoes wear off with their unique indicators. Enjoy comfort for long-time use due to Honeywell Otter Premium's modular insole system created to offer a perfect fit for everyone.



PROTECT AIR S1P HRO SRC ESD

- Extra wide metallic toecap
- TPU coat
- Low-cut style
- Breathable mesh material
- Mesh lining with foam
- Stainless steel anti-perforation interlayer
- PU/Nitrile outsole
- Wear off indicators
- HRO marking: resistance to hot contact
- ESD marking: electrical resistance
- EN ISO 20345:2011 S1P HRO SRC ESD
- DGUV 112-191 coming soon



PERFORM BEYOND STANDARDS

After demonstrating compliance with all applicable regulations, Honeywell has gone the extra mile to prove that the Otter Premium range takes you a step ahead of requirements*:

- 1. Longitudinal flexibility – strength to bend the sole up to 45°** – The longitudinal flexing compliance of Protect Air has an average value of 2.62 daN, which translates into excellent flexibility, more comfort and less fatigue.
- 2. The breathability of the whole shoe** – The average amount of water (sweat) that evaporates from Protect Air is of 3.13 grams in one hour, which translates into reduced sweating, improved comfort and high breathability.
- 3. Internal torsion rigidity in the waist area** – Tests have shown that Protect Air provides improved comfort and safety outdoors by preventing foot twisting when walking: 4.2 N.m.
- 4. The sole's transfer coefficient** – The impact transmitted through the sole to the wearer shows Protect Air's impact energy absorption is excellent: the heel absorbs 24% of the impact in the outsole.
- 5. The energy return from the sole** – Protect Air causes less fatigue due to the improved sole, which absorbs, stores and returns kinetic energy to the wearer, supporting the muscles during the natural walking motion:
 - the transmitted energy is of 2,515 N
 - the restored energy is of 1,656 N
 - the percentage of transmitted energy is of 66%

*) Test results represent average values.

ALL-ROUND PERFORMANCE – AT YOUR FEET

TOECAP

- Extra wide metallic toecap
- Durable, metallic, anti-perforation interlayer (1,100 N)

SOLE

- 8 wear-off indicators on the outer layer
- Heel shock absorption system
- PU/Nitrile outsole
- On steel floor: 0.16 heel (minimum standard 0.13)
- Flat: 0.18 (minimum standard 0.18)
- On ceramic floor: 0.37 heel (minimum standard 0.28)
- Flat: 0.37 (minimum standard 0.32)
- Energy absorption capacity >20 J
- Abrasion resistance: loss in volume <150 mm³ (under a 10 Newtons (1 kg) load)
- Elongation at break: 650%
- Resistance to repeated flexion optimized: >30,000
- Flexometer tested – standard: >30,000
- Resistance to fuel oil

TECHNICAL SPECIFICATIONS AND STANDARDS:

- European Regulation: (EU) 2016/425*
- Standard: EN ISO 20345:2011**
- Quality assurance: ISO 9001 Version 2015***
- Marking: S1P HRO SRC ESD
- Average weight for 1 shoe 42 size: 692 g

*) <https://osha.europa.eu/en/safety-and-health-legislation>

**) <https://www.iso.org/home.html>

***) <https://group.bureauveritas.com/>

OUTSOLE SLIP RESISTANCE PERFORMANCE

MARKING	SURFACE	LUBRICANT	FRICTION FACTOR: FLAT
SRA	Ceramic plates	Sodium lauryl sulfate	0.37 (minimum requirement 0.32)
SRB	Steel	Glycerol	0.18 (mimimum standard 0.18)
SRC	Meets requirements of the above 2 tests (SRA plus SRB)		

ORDERING INFORMATION

DESCRIPTION	REF.	SIZE
Protect Air S1P HRO SRC ESD	65 516 36	36-48

For More Information

www.honeywellsafety.com

HONEYWELL SAFETY PRODUCTS UNITED KINGDOM

Honeywell Safety Products UK LTD
Edison Road
Basingstoke RG21 6QD
Phone: +44 (0) 1256 693 200
Fax: +44 (0) 1256 693 300
Email: info-uk.hsp@honeywell.com

HONEYWELL SAFETY PRODUCTS NORDICS

Honeywell Safety Products Nordic AB
Strandbadsvägen 15
SE-252 29 Helsingborg – Sverige
Phone: +46 (0) 424480433
Email: info-nordic.hsp@honeywell.com

HONEYWELL SAFETY PRODUCTS BENELUX

Honeywell Safety Products Benelux BV
Hermeslaan 1H – 1831 Diegem
Phone: +32 (0) 2 728 2117
Fax: +32 (0) 2 728 2396
Email: info-benelux.hsp@honeywell.com