

## NOTES:

- 1. WHEN INSTALLING THIS UNIT, LOCAL CODES SHOULD BE ADHERED TO FOR INSTALLATION DIMENSIONS (LOCATIONS), WASTE AND SUPPLY REQUIREMENTS OTHER THAN SHOWN.
- TO COMPLY WITH ANSI Z358.1-2014 FOR EMERGENCY EYEWASH OR EYE/FACE WASH: EYEWASH OR EYE/FACE WASH SHALL BE POSITIONED SUCH THAT FLUSHING FLUID PATTERN IS NOT LESS THAN 33" (838mm) AND NO GREATER THAN 53" (1346 mm) FROM SURFACE ON WHICH USER STANDS; AND 6.0" (153mm) MINIMUM FROM WALL OR NEAREST OBSTRUCTION.

TO COMPLY WITH DIN EN 15154-2 FOR PLUMBED-IN EYEWASH: EYEWASH SHALL BE POSITIONED SUCH THAT OUTLET NOZZLES ARE NOT LESS THAN 31.5" (800mm) AND NO GREATER THAN 47.24" (1200 mm) FROM SURFACE ON WHICH USER STANDS; AND 5.9" (150mm) MINIMUM FROM WALL OR NEAREST OBSTRUCTION.

- 3. DIMENSIONS MAY VARY BY ±1/2" (13 mm).
- 4. DIMENSIONS IN BRACKETS, IN DRAWING SPACE, ARE METRIC [mm].

