



## 3M™ PELTOR™ Rechargeable Li-Ion Battery Pack, ACK081B/1

### Product Description



The 3M PELTOR rechargeable Li-Ion battery pack to be used for certain 3M products, such as WS LiteCom Plus, WS LiteCom Pro III, WS Adapter G3 among others, please refer to the user instruction for your product.

Battery pack is delivered in “shipping-mode” to reduce self-discharge and will not start until the charger is attached. When the red LED lights up, the battery pack is turned on and charging starts.

When battery is not connected to a product all connectors are de-energized to minimize any corrosion or short circuit risks.

To be compliant with the European Common Charger Directive, the battery can only be charged outside the product. When battery is attached to the product the charging function is disabled electronically. To charge the battery, remove it from the product and connect it to the the charger cable. The LED will flash green and red if the charging cable is connected while battery is in the product.

### Key Features

- Increased capacity, 3,7 V 2150 mAh, 8Wh,
- De-energized connectors when battery is not connected to a product.
- Delivered in “shipping-mode.”
- Fully compatible with ACK081.

### Standards and Approvals

Hereby, 3M Svenska AB declares that the product is in compliance with appropriate directives or regulations to fulfill the requirements for the CE marking.

The full text of the EU declaration of conformity is available at the following internet address: [www.3M.com/PELTOR/DOC](http://www.3M.com/PELTOR/DOC). A copy of the declaration of conformity and additional information required in the directives or regulations can also be obtained by contacting 3M in the country of purchase.

### Models

Article Number	Description	3M ID
ACK081B/1	3M PELTOR Rechargeable Li-Ion battery pack	7100330766

Article Number	Description	3M ID
AL2AI/SP	3M PELTOR charging cable	7100088372
FR08	3M PELTOR 5V USB power supply	7000108521

## Spare Part

Article Number	Description	3M ID
210004/10	Clip, 10 ea./pack	7100231593

## Technical Data Specifications

Materials	Value
Weight	80g
Battery enclosure	ABS
Battery	Rechargeable Li-Ion 3,7V 2150mAh, 8Wh
Recharging time	Approx 4h (full recharge)

Storage	Value
Operation temperature	-20 °C (-4 °F) to 55 °C (131 °F)
Charging temperature	0 °C (32 °F) to 45 °C (113 °F)
Storage temperature	-20 °C (-4 °F) to 40 °C (104 °F)

Note: While stored, recharge battery every 6 months not to lose capacity.

User limitation: Never modify or alter this product

### Included in the box:

- 1x 3M PELTOR ACK081B
- 1 x User instruction

## Warranty and Important Notice

### Warranty

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office.

### Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The User is responsible for determining the suitability of the products for their intended use. 3M acknowledges the respective Trademark Owners' rights in this literature.



**Personal Safety Division**  
3M Svenska AB, Box 2341  
SE-331 02 Värnamo  
Sweden

Internet [www.3M.com/PELTOR](http://www.3M.com/PELTOR)  
Phone: +46 (0)370-65 65 00

3M PSD products are occupational use only. In Europe, 3M PELTOR products may also be appropriate for certain non-work uses. Always read and follow User instructions.

Please recycle. Printed in Sweden.  
© 3M 2025. All rights reserved.  
3M and PELTOR are trademarks of 3M Company and its affiliates.  
DS24001 rev.a